


# 430W

Positive Power Tolerance

Class leading power output **-0 to +3%**



## True American Quality True American Brand

Mission Solar Energy is headquartered in San Antonio, Texas where we manufacture our modules. We produce American, high-quality solar modules ensuring the highest-in-class power output and best-in-class reliability. Our product line is tailored for residential, commercial and utility applications. Every Mission Solar Energy solar module is certified and surpasses industry standard regulations, proving excellent performance over the long term.

**Demand the best. Demand Mission Solar Energy.**



### Certified Reliability

- Tested to UL 61730 & IEC Standards
- PID resistant
- Resistance to salt mist corrosion



### Advanced Technology

- 9 Busbar
- Passivated Emitter Rear Contact
- Ideal for all applications



### Extreme Weather Resilience

- Up to 5,400 Pa front load & 3,600 Pa back load
- Tested load to UL 61730
- 40 mm frame



### BAA Compliant for Government Projects

- Buy American Act
- American Recovery & Reinvestment Act

### FRAME-TO-FRAME WARRANTY

Degradation guaranteed not to exceed 2% in year one and 0.58% annually from years two to 30 with 84.08% capacity guaranteed in year 25. For more information, visit [www.missionsolar.com/warranty](http://www.missionsolar.com/warranty)


### CERTIFICATIONS

CEC




If you have questions or concerns about certification of our products in your area, please contact Mission Solar Energy.

UL 61730 / IEC 61215 / IEC 61730 / IEC 61701



**BASIC DIMENSIONS**

[UNITS: MM/IN]



**ELECTRICAL SPECIFICATION**

PRODUCT TYPE	MSExxxSX9Z (xxx = P <sub>max</sub> )				
Power Output	P <sub>max</sub>	W <sub>p</sub>	425	430	435
Module Efficiency	%		19.3	19.6	19.8
Tolerance	%		-0/+3	-0/+3	-0/+3
Short Circuit Current	I <sub>sc</sub>	A	11.42	11.47	11.50
Open Circuit Voltage	V <sub>oc</sub>	V	49.04	49.26	49.40
Rated Current	I <sub>mp</sub>	A	10.78	10.86	10.90
Rated Voltage	V <sub>mp</sub>	V	39.44	39.59	39.92
Fuse Rating	A		20	20	20
System Voltage	V		1500	1500	1500


**TEMPERATURE COEFFICIENTS**

Normal Operating Cell Temperature (NOCT)	46.08°C (±3.7%)
Temperature Coefficient of P <sub>max</sub>	-0.347%/°C
Temperature Coefficient of V <sub>oc</sub>	-0.261%/°C
Temperature Coefficient of I <sub>sc</sub>	0.043%/°C

**CURRENT-VOLTAGE CURVE**

MSE425SX9Z: 425WP, 72 CELL SOLAR MODULE

Current-voltage characteristics with dependence on irradiance and module temperature



**OPERATING CONDITIONS**

Maximum System Voltage	1,500Vdc
Operating Temperature Range	-40°F to 185°F (-40°C to +85°C)
Maximum Series Fuse Rating	20A
Fire Safety Classification	Type 1*
Front & Back Load (UL Standard)	5400 Pa front and 3600 Pa back load Tested to UL 61730
Hail Safety Impact Velocity	25mm at 23 m/s

\*Mission Solar Energy uses quality sourced materials that result in a Type 1 fire rating. Please note, the 'Fire Class' Rating is designated for the fully-installed PV system, which includes, but is not limited to, the module, the type of mounting used, pitch and roof composition.

**MECHANICAL DATA**

Solar Cells	P-type mono-crystalline silicon
Cell Orientation	72 cells (6x12)
Module Dimension	2,086mm x 1,054mm x 40mm
Weight	51.6 lbs. (23.4 kg)
Front Glass	3.2mm tempered, low-iron, anti-reflective
Frame	40mm Anodized
Encapsulant	Ethylene vinyl acetate (EVA)
Junction Box	Protection class IP67 with 3 bypass-diodes
Cable	1.4m, Wire 4mm <sup>2</sup> (12AWG)
Connector	MC4 Staubli PV-KBT4-EVO 2/6II-UR and PV-KST4-EVO 2/6II-UR, Renhe RHC2xMzC

**CERTIFICATIONS AND TESTS**

IEC	61215, 61730, 61701
UL	61730



CEC



Mission Solar Energy

8303 S. New Braunfels Ave., San Antonio, Texas 78235  
www.missionsolar.com | info@missionsolar.com

**SHIPPING INFORMATION**

Container Feet	Ship To	Pallet	Panels	425W Bin
53'	Most States	28	728	309.40 kW
Double Stack	CA	25	650	276.25 kW

**PALLET [26 PANELS]**

Weight	Height	Width	Length
1,450 lbs. (657 kg)	47.5 in (120.65 cm)	46 in (116.84 cm)	83.75 in (212.72 cm)